

Power Accessories

AC Power Supplies

Locking barrel plugs, 12 VDC 0.5 A, 100-240 VAC (Switch-Mode)

Model Name	PWR-12050-WPUSJP-S1	PWR-12050-WPEU-S1	PWR-12050-WPUK-S1	PWR-12050-WPAU-S1	PWR-12050-WPCN-S1
					
Input Rating					
I/P	100 to 240 VAC 50 to 60 Hz	100 to 240 VAC 50 to 60 Hz	100 to 240 VAC 50 to 60 Hz	100 to 240 VAC 50 to 60 Hz	100 to 240 VAC 50 to 60 Hz
Input Plug					
Plug Type	US/JP	EU	UK	AU	CN
Output Rating					
O/P	0.5 A @ 12 VDC	0.5 A @ 12 VDC	0.5 A @ 12 VDC	0.5 A @ 12 VDC	0.5 A @ 12 VDC
Output Plug					
Connector Type	S-Type 5.5/2.1/7.5	S-Type 5.5/2.1/7.5	S-Type 5.5/2.1/7.5	S-Type 5.5/2.1/7.5	S-Type 5.5/2.1/7.5
Outer Diameter	5.5±0.1 mm (0.22±0.004 in)	5.5±0.1 mm (0.22±0.004 in)	5.5±0.1 mm (0.22±0.004 in)	5.5±0.1 mm (0.22±0.004 in)	5.5±0.1 mm (0.22±0.004 in)
Inner Diameter	2.1±0.1 mm (0.08±0.004 in)	2.1±0.1 mm (0.08±0.004 in)	2.1±0.1 mm (0.08±0.004 in)	2.1±0.1 mm (0.08±0.004 in)	2.1±0.1 mm (0.08±0.004 in)
Physical Characteristics					
Dimensions (L x W x H)	64 x 40.5 x 47.5 mm (2.52 x 1.59 x 1.87 in)	64 x 40.5 x 68.7 mm (2.52 x 1.59 x 2.71 in)	64 x 40.5 x 56.2 mm (2.52 x 1.59 x 2.21 in)	64 x 40.5 x 58.5 mm (2.52 x 1.59 x 2.30 in)	64 x 40.5 x 46.5 mm (2.52 x 1.59 x 1.83 in)
Packaged Dimensions (L x W x H)	83 x 50 x 70 mm (3.27 x 1.97 x 2.76 in)	83 x 50 x 70 mm (3.27 x 1.97 x 2.76 in)	83 x 50 x 70 mm (3.27 x 1.97 x 2.76 in)	83 x 50 x 70 mm (3.27 x 1.97 x 2.76 in)	83 x 50 x 70 mm (3.27 x 1.97 x 2.76 in)
Weight	70 g (0.15 lb)	70 g (0.15 lb)	70 g (0.15 lb)	70 g (0.15 lb)	70 g (0.15 lb)
Cord Length	1530±100 mm (60.24±3.94 in)	1530±100 mm (60.24±3.94 in)	1530±100 mm (60.24±3.94 in)	1530±100 mm (60.24±3.94 in)	1530±100 mm (60.24±3.94 in)
Environmental Limits					
Operating Temperature	0 to 40°C (32 to 104°F)	0 to 40°C (32 to 104°F)	0 to 40°C (32 to 104°F)	0 to 40°C (32 to 104°F)	0 to 40°C (32 to 104°F)
Storage Temperature	-10 to 70°C (14 to 158°F)	-10 to 70°C (14 to 158°F)	-10 to 70°C (14 to 158°F)	-10 to 70°C (14 to 158°F)	-10 to 70°C (14 to 158°F)
Regulatory Approvals					
Safety	CE/FCC/UL/GS/PSE/RCM/CCC	CE/FCC/UL/GS/PSE/RCM/CCC	CE/FCC/UL/GS/PSE/RCM/CCC	CE/FCC/UL/GS/PSE/RCM/CCC	CE/FCC/UL/GS/PSE/RCM/CCC
Related Products					
Related Products	NPort 5110A, NPort 5130A, NPort 5150A, NPort 5210A, NPort 5230A, NPort 5250A, NPort Z2150/Z3150, NPort W2150A/W2250A, NPort P5110A				

DC Power Cord

Locking barrel plug to bare wires

CBL-PJ21NOPEN-BK-30

Cable Length: 300±20 mm (11.81±0.79 in)



AC Power Supplies

Locking barrel plugs, 12 VDC, 3 A 100-240 VAC (Switch-Mode)

Model Name	PWR-12300-WPUSJP-S1	PWR-12300-WPEU-S1	PWR-12300-WPUK-S1	PWR-12300-WPAU-S1	PWR-12300-WPCN-S1
					
Input Rating					
I/P	100-240 VAC 50-60 Hz	100-240 VAC 50-60 Hz	100-240 VAC 50-60 Hz	100-240 VAC 50-60 Hz	100-240 VAC 50-60 Hz
Input Plug					
Plug Type	US/JP	EU	UK	AU	CN
Output Rating					
O/P	3 A @ 12 VDC	3 A @ 12 VDC	3 A @ 12 VDC	3 A @ 12 VDC	3 A @ 12 VDC
Output Plug					
Connector Type	S-Type 5.5/2.1/7.5	S-Type 5.5/2.1/7.5	S-Type 5.5/2.1/7.5	S-Type 5.5/2.1/7.5	S-Type 5.5/2.1/7.5
Outer Diameter	5.5±0.1 mm (0.22±0.004 in)	5.5±0.1 mm (0.22±0.004 in)	5.5±0.1 mm (0.22±0.004 in)	5.5±0.1 mm (0.22±0.004 in)	5.5±0.1 mm (0.22±0.004 in)
Inner Diameter	2.1±0.1 mm (0.08±0.004 in)	2.1±0.1 mm (0.08±0.004 in)	2.1±0.1 mm (0.08±0.004 in)	2.1±0.1 mm (0.08±0.004 in)	2.1±0.1 mm (0.08±0.004 in)
Physical Characteristics					
Dimensions (L x W x H)	74 x 43.5 x 52.3 mm (2.91 x 1.71 x 2.06 in)	74 x 43.5 x 73.5 mm (2.91 x 1.71 x 2.89 in)	74 x 43.5 x 61 mm (2.91 x 1.71 x 2.40 in)	74 x 43.5 x 63.3 mm (2.91 x 1.71 x 2.49 in)	74 x 43.5 x 51.3 mm (2.91 x 1.71 x 2.02 in)
Packaged Dimensions (L x W x H)	100 x 60 x 90 mm (3.94 x 2.36 x 3.54 in)	100 x 60 x 90 mm (3.94 x 2.36 x 3.54 in)	100 x 60 x 90 mm (3.94 x 2.36 x 3.54 in)	100 x 60 x 90 mm (3.94 x 2.36 x 3.54 in)	100 x 60 x 90 mm (3.94 x 2.36 x 3.54 in)
Weight	163 g (0.36 lb)	163 g (0.36 lb)	163 g (0.36 lb)	163 g (0.36 lb)	163 g (0.36 lb)
Cord Length	1530±200 mm (60.24±7.87 in)	1530±200 mm (60.24±7.87 in)	1530±200 mm (60.24±7.87 in)	1530±200 mm (60.24±7.87 in)	1530±200 mm (60.24±7.87 in)
Environmental Limits					
Operating Temperature	0 to 40°C (32 to 104°F)	0 to 40°C (32 to 104°F)	0 to 40°C (32 to 104°F)	0 to 40°C (32 to 104°F)	0 to 40°C (32 to 104°F)
Storage Temperature	-20 to 70°C (-4 to 158°F)	-20 to 70°C (-4 to 158°F)	-20 to 70°C (-4 to 158°F)	-20 to 70°C (-4 to 158°F)	-20 to 70°C (-4 to 158°F)
Regulatory Approvals					
Safety	FCC/CE/UL/GS/CCC/RCM/PSE	FCC/CE/UL/GS/CCC/RCM/PSE	FCC/CE/UL/GS/CCC/RCM/PSE	FCC/CE/UL/GS/CCC/RCM/PSE	FCC/CE/UL/GS/CCC/RCM/PSE
Related Products					
Related Products	UPort 204, UPort 207, UPort 404, UPort 407				

A
 Accessories > Power Accessories

DC Power Cord

Locking barrel plug to bare wires

CBL-PJ21NOPEN-BK-30

Cable Length: 300±20 mm (11.81±0.79 in)



AC Power Supplies

Non-locking barrel plugs, 12 VDC 0.5 A, 100-240 VAC (Switch-Mode)

Model Name	PWR-12050-WPUSJP-S2	PWR-12050-WPEU-S2	PWR-12050-WPUK-S2	PWR-12050-WPAU-S2	PWR-12050-WPCN-S2
					
Input Rating					
I/P	100 to 240 VAC 50 to 60 Hz	100 to 240 VAC 50 to 60 Hz	100 to 240 VAC 50 to 60 Hz	100 to 240 VAC 50 to 60 Hz	100 to 240 VAC 50 to 60 Hz
Input Plug					
Plug Type	US/JP	EU	UK	AU	CN
Output Rating					
O/P	0.5 A @ 12 VDC	0.5 A @ 12 VDC	0.5 A @ 12 VDC	0.5 A @ 12 VDC	0.5 A @ 12 VDC
Output Plug					
Connector Type	L-Type 5.5/2.1/9.0	L-Type 5.5/2.1/9.0	L-Type 5.5/2.1/9.0	L-Type 5.5/2.1/9.0	L-Type 5.5/2.1/9.0
Outer Diameter	5.5±0.1 mm (0.22±0.004 in)	5.5±0.1 mm (0.22±0.004 in)	5.5±0.1 mm (0.22±0.004 in)	5.5±0.1 mm (0.22±0.004 in)	5.5±0.1 mm (0.22±0.004 in)
Inner Diameter	2.1±0.1 mm (0.08±0.004 in)	2.1±0.1 mm (0.08±0.004 in)	2.1±0.1 mm (0.08±0.004 in)	2.1±0.1 mm (0.08±0.004 in)	2.1±0.1 mm (0.08±0.004 in)
Physical Characteristics					
Dimensions (L x W x H)	64 x 40.5 x 30 mm (2.52 x 1.59 x 1.18 in)	64 x 40.5 x 68.7 mm (2.52 x 1.59 x 2.71 in)	64 x 40.5 x 56.2 mm (2.52 x 1.59 x 2.21 in)	64 x 40.5 x 58.5 mm (2.52 x 1.59 x 2.30 in)	64 x 40.5 x 46.5 mm (2.52 x 1.59 x 1.83 in)
Packaged Dimensions (L x W x H)	83 x 50 x 70 mm (3.27 x 1.97 x 2.76 in)	83 x 50 x 70 mm (3.27 x 1.97 x 2.76 in)	83 x 50 x 70 mm (3.27 x 1.97 x 2.76 in)	83 x 50 x 70 mm (3.27 x 1.97 x 2.76 in)	83 x 50 x 70 mm (3.27 x 1.97 x 2.76 in)
Weight	70 g (0.15 lb)	70 g (0.15 lb)	70 g (0.15 lb)	70 g (0.15 lb)	70 g (0.15 lb)
Cord Length	1830±100 mm (72.05±3.94 in)	1830±100 mm (72.05±3.94 in)	1830±100 mm (72.05±3.94 in)	1830±100 mm (72.05±3.94 in)	1830±100 mm (72.05±3.94 in)
Environmental Limits					
Operating Temperature	0 to 40°C (32 to 104°F)	0 to 40°C (32 to 104°F)	0 to 40°C (32 to 104°F)	0 to 40°C (32 to 104°F)	0 to 40°C (32 to 104°F)
Storage Temperature	-10 to 70°C (14 to 158°F)	-10 to 70°C (14 to 158°F)	-10 to 70°C (14 to 158°F)	-10 to 70°C (14 to 158°F)	-10 to 70°C (14 to 158°F)
Regulatory Approvals					
Safety	CE/FCC/UL/RMC/PSE/CCC	CE/FCC/UL/RMC/PSE/CCC	CE/FCC/UL/RMC/PSE/CCC	CE/FCC/UL/RMC/PSE/CCC	CE/FCC/UL/RMC/PSE/CCC
Regulatory Products					
Related Products	NPort 5110, NPort 5130, NPort 5150, NPort 5210, NPort 5230, NPort 5232, NPort 5232I, MGate MB3180, MGate MB3280, DE-211, DE-311, A52, A53, MiiNePort E1-ST				

DC Power Cord

Non-locking barrel plug to bare wires

CBL-PJTB-10

Cable Length: 100±20 mm (3.94±0.79 in)



AC Power Supplies

Non-locking barrel plugs, 12 VDC 1.25/1.5 A, 100-240 VAC

Model Name	PWR-12125-USJP-S1	PWR-12150-EU-S2	PWR-12150-UK-S2	PWR-12150-AU-S2	PWR-12150-CN-S1
					
Input Rating					
I/P	100 to 240 VAC 50 to 60 Hz	100 to 240 VAC 50 to 60 Hz	100 to 240 VAC 50 to 60 Hz	100 to 240 VAC 50 to 60 Hz	100 to 240 VAC 50 to 60 Hz
Input Plug					
Plug Type	US/JP	EU	UK	AU	CN
Output Rating					
O/P	1.25 A @ 12 VDC	1.5 A @ 12 VDC	1.5 A @ 12 VDC	1.5 A @ 12 VDC	1.5 A @ 12 VDC
Output Plug					
Connector Type	L-Type 5.5/2.1/9.5	L-Type 5.5/2.1/9.0	S-Type 5.5/2.1/9.0	L-Type 5.5/2.1/9.0	L-Type 5.5/2.1/9.0
Outer Diameter	5.5±0.1 mm (0.22±0.004 in)	5.5±0.1 mm (0.22±0.004 in)	5.5±0.1 mm (0.22±0.004 in)	5.5±0.1 mm (0.22±0.004 in)	5.5±0.1 mm (0.22±0.004 in)
Inner Diameter	2.1±0.1 mm (0.08±0.004 in)	2.1±0.1 mm (0.08±0.004 in)	2.1±0.1 mm (0.08±0.004 in)	2.1±0.1 mm (0.08±0.004 in)	2.1±0.1 mm (0.08±0.004 in)
Physical Characteristics					
Dimensions (L x W x H)	74 x 43.5 x 52.5 mm (2.91 x 1.71 x 2.07 in)	70 x 45 x 66.5 mm (2.76 x 1.77 x 2.62 in)	70 x 48 x 60 mm (2.76 x 1.89 x 2.36 in)	70 x 55 x 56 mm (2.76 x 2.17 x 2.21 in)	70 x 45 x 54 mm (2.76 x 1.77 x 2.13 in)
Packaged Dimensions (L x W x H)	100 x 60 x 90 mm (3.94 x 2.36 x 3.54 in)	100 x 60 x 90 mm (3.94 x 2.36 x 3.54 in)	100 x 60 x 90 mm (3.94 x 2.36 x 3.54 in)	100 x 60 x 90 mm (3.94 x 2.36 x 3.54 in)	100 x 60 x 90 mm (3.94 x 2.36 x 3.54 in)
Weight	108 g (0.24 lb)	200 g (0.44 lb)	200 g (0.44 lb)	200 g (0.44 lb)	200 g (0.44 lb)
Cord Length	1530±100 mm (60.24±3.84 in)	1800±200 mm (70.87±7.87 in)	1800±200 mm (70.87±7.87 in)	1800±200 mm (70.87±7.87 in)	1800±200 mm (70.87±7.87 in)
Environmental Limits					
Operating Temperature	0 to 40°C (32 to 104°F)	0 to 40°C (32 to 104°F)	0 to 40°C (32 to 104°F)	0 to 40°C (32 to 104°F)	0 to 40°C (32 to 104°F)
Storage Temperature	-20 to 70°C (-4 to 158°F)	-20 to 70°C (-4 to 158°F)	-20 to 70°C (-4 to 158°F)	-20 to 70°C (-4 to 158°F)	-20 to 70°C (-4 to 158°F)
Regulatory Approvals					
Safety	CE/FCC/UL/RMC/PSE/GS	CE/GS	CE	RMC	CCC
Related Products					
Related Products	NPort 5410, NPort 5430, NPort 5430I, NPort 5450, NPort 5450I, MGate MB3480				

A
 Accessories > Power Accessories

DC Power Cord

Non-locking barrel plug to bare wires

CBL-PJTB-10

Cable Length: 100±20 mm (3.94±0.79 in)








AC Power Supplies

Desktop type power adapters

Model Name	PWR-12200-DT-S1	PWR-12125-DT-S2
		
Input Rating		
I/P	100 to 240 VAC 50 to 60 Hz	100 to 240 VAC 50 to 60 Hz
Input Plug		
Plug Type	Desktop	Desktop
Output Rating		
O/P	2 A @ 12 VDC	1.25 A @ 12 VDC
Output Plug		
Connector Type	S-Type 5.5/2.1/7.5	S-Type 5.5/2.1/7.5
Outer Diameter	5.5±0.1 mm (0.22±0.004 in)	5.5±0.1 mm (0.22±0.004 in)
Inner Diameter	2.1±0.1 mm (0.08±0.004 in)	2.1±0.1 mm (0.08±0.004 in)
Physical Characteristics		
Dimensions (L x W x H)	110.8 x 51.8 x 32 mm (4.36 x 2.04 x 1.26 in)	75 x 47.5 x 27.3 mm (2.95 x 1.87 x 1.07 in)
Packaged Dimensions (L x W x H)	135 x 75 x 35 mm (5.31 x 2.95 x 1.38 in)	100 x 70 x 51.5 mm (3.94 x 2.76 x 2.03 in)
Weight	200 g (0.44 lb)	200 g (0.44 lb)
Cord Length	1800±200 mm (70.87±7.87 in)	1530±100 mm (60.24±3.84 in)
Environmental Limits		
Operating Temperature	0 to 40°C (32 to 104°F)	0 to 40°C (32 to 104°F)
Storage Temperature	-20 to 70°C (-4 to 158°F)	-10 to 70°C (14 to 158°F)
Regulatory Approvals		
Safety	Efficiency Level 5: CE/FCC/UL/PSE/RCM/CCC Efficiency Level 6: CE/FCC/UL/PSE	CE/FCC/UL/PSE/GS
Related Products		
Related Products	NPort 5610-8-DT, NPort 5610-8-DT-J, NPort 5650-8-DT, NPort 5650-8-DT-J, NPort 5650I-8-DT, NPort 5610-8-DTL, NPort 5650-8-DTL, NPort 5650I-DTL	NPort 6150, NPort 6250-M-SC, NPort 6250, NPort 6250-S-SC, NPort 6450, UPort 1250I, UPort 1450, UPort 1450I, UPort 1610-8, UPort 1650-8

Note: PWR-12200-DT-S1 and PWR-12125-DT-S2 not included with power cord

Model Name	PWC-C13US-3B-183	PWC-C-13EU-3B-183 (CEE 7/7 to IEC C13)	PWC-C13UK-3B-183	PWC-C13JP-3B-183	PWC-C13AU-3B-183	PWC-C13CN-3B-183
						
Region	US	EU	UK	JP	AU	CN
Voltage	125 V	250 V	250 V	125 V	250 V	250 V
Thickness	6.3±0.2 mm (0.25±0.01 in)	6.7±0.2 mm (0.26±0.01 in)	6.7±0.2 mm (0.26±0.01 in)	7.0±0.2 mm (0.28±0.01 in)	6.7±0.2 mm (0.26±0.01 in)	6.7±0.2 mm (0.26±0.01 in)
Max. Current	10 A	10 A	10 A	7 A	10 A	10 A
Length	1830±30 mm (72.05±1.18 in)	1830±30 mm (72.05±1.18 in)	1830±30 mm (72.05±1.18 in)	1830±30 mm (72.05±1.18 in)	1830±30 mm (72.05±1.18 in)	1830±30 mm (72.05±1.18 in)
Related Products	CN2500 Series, NPort 6600 Series, NPort 5600 Series, PWR-12200-DT-S1					

Model Name	PWC-C7US-2B-183	PWC-C7EU-2B-183	PWC-C7UK-2B-183	PWC-C7JP-2B-183	PWC-C7AU-2B-183	PWC-C7CN-2B-183
						
Region	US	EU	UK	JP	AU	CN
Length	1830±200 mm (72.05±7.87 in)	1830±200 mm (72.05±7.87 in)	1830±200 mm (72.05±7.87 in)	1830±200 mm (72.05±7.87 in)	1830±200 mm (72.05±7.87 in)	1830±200 mm (72.05±7.87 in)
Related Products	PWR-12125-DT-S2	PWR-12125-DT-S2	PWR-12125-DT-S2	PWR-12125-DT-S2	PWR-12125-DT-S2	PWR-12125-DT-S2

Locking barrel plug to bare wires

CBL-PJ21NOPEN-BK-30

Cable Length: 300±20 mm (11.81±0.79 in)



Wide Temperature AC Power Supplies

Locking barrel plug, 12VDC 1.5A, 100-240VAC (Switch-Mode)

Model Name	PWR-12150-USJP-SA-T	PWR-12150-EU-SA-T	PWR-12150-UK-SA-T	PWR-12150-AU-SA-T	PWR-12150-CN-SA-T
Accessories Image					
Input Rating	100 to 240 VAC, 50 to 60 Hz				
I/P	100 to 240 VAC, 50 to 60 Hz				
Input Plug	US/JP, EU, UK, AU, CN				
Plug Type	US/JP, EU, UK, AU, CN				
Output Rating	1.5A @ 12VDC				
O/P	1.5A @ 12VDC				
Protection Requirements	Over current protection/ Over voltage protection				
Protection	Over current protection/ Over voltage protection				
Output Plug	L-Type 5.5/2.1/7.5				
Connector Type	L-Type 5.5/2.1/7.5				
Outer Diameter	5.5±0.1 mm (0.22±0.004 in)				
Inner Diameter	2.1±0.1 mm (0.08±0.004 in)				
Physical Characteristics					
Dimensions (L x W x H)	32 x 70.3 x 88 mm (1.26 x 2.77 x 3.46 in)				
Weight	200 g (0.44 lb)				
Cord Length	1500±200 mm (59.06±7.87 in)				
Environmental Limits					
Operating Temperature	-40 to 75°C (-40 to 167°F)				
Regulatory Approvals	FCC/UL/PSE, TUV/CE/GS, CE, RCM, CCC				
Safety	FCC/UL/PSE, TUV/CE/GS, CE, RCM, CCC				
Related Products	NPort 5110-T, NPort 5450-T, NPort 5450-I, NPort 5110A-T, NPort 5610-8-DTL-T, NPort 5650-8-DTL-T, NPort 5650I-8-DTL-T, NPort 5130A-T, NPort 5150A-T, NPort 5210A-T, NPort 5230A-T, NPort 5250A-T, NPort 6100-T, NPort 6200-T, NPort 6400-T				

Power Supplies

24/48 VDC power supplies for installation on a DIN rail

Model Name	24 VDC DIN-Rail Power Supplies					48 VDC DIN-Rail Power Supplies			
	DR-4524	DR-75-24	DR-120-24	MDR-40-24	MDR-60-24	DR-75-48	DR-120-48	DRP-240-48	SDR-480P-48
Accessories Image									
Physical Characteristics and Temperature Limits									
Dimensions	78 x 67 x 93 mm (3.07 x 2.64 x 3.66 in)	55.5 x 100 x 125.2 mm (2.19 x 3.94 x 4.93 in)	65.5 x 100 x 125.2 mm (2.58 x 3.94 x 4.93 in)	40 x 90 x 100 mm (1.57 x 3.54 x 3.94 in)	40 x 90 x 100 mm (1.57 x 3.54 x 3.94 in)	55.5 x 100 x 125.2 mm (2.19 x 3.94 x 4.93 in)	65.5 x 100 x 125.2 mm (2.58 x 3.94 x 4.93 in)	125.5 x 125.5 x 100 mm (4.94 x 4.94 x 3.94 in)	85.5 x 125.2 x 128.5 mm (3.37 x 4.93 x 5.06 in)
Weight	400 g (0.88 lb)	550 g (1.21 lb)	650 g (1.43 lb)	260 g (0.57 lb)	280 g (0.62 lb)	550 g (1.21 lb)	650 g (1.43 lb)	1.2 kg (2.65 lb)	1.6 kg (3.53 lb)
Operating Temperature	-10 to 50°C (14 to 122°F)	-10 to 60°C (14 to 140°F)		-20 to 70°C (-4 to 158°F)		-10 to 60°C (14 to 140°F)		-10 to 70°C (14 to 158°F)	-25 to 70°C (-13 to 158°F)
Relative Humidity	20 to 90% RH	20 to 90% RH		20 to 90% RH		20 to 90% RH		20 to 90% RH	10 to 95% RH
Power Requirements									
Wattage	45 W	75 W	120 W	40 W	60 W	75 W	120 W	240 W	480 W (current sharing up to 3840 W)
Input Voltage	85-264 VAC (47-63 Hz), or 120-370 VDC		88-132 VAC, or 176-264 VAC (47-63 Hz) by switch, or 248-370 VDC	85-264 VAC (47-63 Hz) or 120-370 VDC		85-264 VAC (27-63 Hz) or 120-370 VDC	88-132 VAC, or 176-264 VAC (47-63 Hz) by switch, or 248-370 VDC	85-264 VAC (47-63 Hz) or 120-370 VDC	90 to 264 VAC or 127 to 370 VDC
Output Power	48 W (24 VDC @ 0-2 A)	76.8 W (24 VDC @ 0-3.2 A)	120 W (24 VDC @ 0-5 A)	40 W (24 VDC @ 0-1.7 A)	60 W (24 VDC @ 0-2.5 A)	76.8 W (48 VDC @ 0-1.6 A)	120 W (48 VDC @ 0-2.5 A)	240 W (48 VDC @ 0-5 A)	480 W (48 VDC @ 0-10 A)
Over-voltage Protection	27.6 to 32.4 V		29 to 33 V	31.2 to 36 V		58 to 65 V		54 to 60 V	56-65 V
Overload Protection	105-150%								
Type	Constant Current Limiting								
Reset	Auto Recovery								
Inrush Current	30 A and 115 V, or 60 A and 230 V								40 A/115 VAC or 80 A/230 VAC
Reliability									
Safety Standards	EN 60950-1, UL 508 approved								
EMC Standards	EN 55022 Class B, EN 61000-4-2/3/4/5/6/8/11, ENV 50204, EN 61000-3-2, EN 50082-2								
Warranty	3 years (see www.moxa.com/warranty)								

A
 Accessories > Power Accessories