

DB9 Adaptor Series

These DB9 adaptors can be used with the following products:

UPort 1100 Series, UPort 1200 Series, UPort 1400 Series, UPort 1600 Series, UPort 2000 Series, NPort 6000 Series, NPort 5000 Series, CN2600 Series, and UC7400 Series.


Details about these products can be found on Moxa's website at www.moxa.com.

Features

- Standard DB9 connector size
- Reliable locking design
- ADP-RJ458P-DB9M and ADP-RJ458P-DB9F
 - > Operating Temperature: -15 to 70°C (5 to 158°F)
 - > Ambient Relative Humidity: 5 to 95% (non-condensing)
- Mini DB9F-to-TB
 - > Operating Temperature: 0 to 70°C (32 to 158°F)
 - > Ambient Relative Humidity: 5 to 95% (non-condensing)



Dimensions



Ordering Information

Mini DB9F-to-TB

DB9 female to terminal block adaptor for RS-422/485 applications



DB9-F	TB
1	2
2	1
3	3
4	4
5	5

ADP-RJ458P-DB9M

RJ45 to DB9 male adaptor



DB9-M	RJ45
1	6
2	5
3	4
4	8
5	3
6	1
7	2
8	7

ADP-RJ458P-DB9F

RJ45 to DB9 female adaptor



DB9-F	RJ45
1	6
2	4
3	5
4	1
5	3
6	8
7	7
8	2